





Microsoft GOLD CERTIFI ISO 14001 Registered


RoHS Compliant

Partne

CC-468

PCI DUAL LPT Printer Port & RS232

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 2 port RS232
- PCI 2.3
- 16 Byte Tx and 16 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options

CC-468: PCI DUAL LPT Printer Port & RS232

Description


This half size card provides two LPT parallel printer ports and two industry standard RS232 serial COM ports. The card has one LPT port and one RS232 port on its bracket, with the second LPT and RS232 ports on a separate bracket attached on a 'fly-lead'. Serial Solutions Device Driver CD contains software for Windows 7, Server 2008, Vista, Server 2003, XP, 2000, Millennium, 98, 95, NT4, Windows 3.x, DOS and OS/2. Informative manuals and sample programs are supplied with full source code on CD!

Brainboxes range of PCI cards support 5V PCI slots and have been superceded by Brainboxes uPCI (universal Peripheral Component Interconnect) range. For every card in the CC range there is a matching card in

Software

Microsoft signed drivers (easy installation & robust operation) for:

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many



+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com

CC-468

PCI DUAL LPT Printer Port & RS232

CC-468Full Specification

Pin1 DCD Pin 2 RXD Pin 3 TXD Pin 4 DTR Pin 5 GND	Ports Connector FIFO size	2 x RS232 Connector DB9 9 Pin Male
Pin 3 RXD Pin 3 TXD Pin 4 DTR		
Pin 3 TXD Pin 4 DTR Pin 5 GND	FIFO size	
Pin 5 GND		16 RX FIFO + 16 TX FIFO
Pin 6 DSR	Operating Distance	EIA - RS232 Standard
Pin 7 RTS Pin 8 CTS Pin 9 R1	Cable	1 port RS232 on fly lead
Port Settings	Baud Rate	115,200
115,200	Data Bits	5,6,7 or 8
>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1 or 2
	Flow Control	
	Tx/Rx Modes	Point to Point
Interface PCI °	OS Compatibility	Microsoft Windows 7 32 bit & 64 bit Editions Windows Server 2008 32 bit & 64 bit Editions Windows Vista 32 bit & 64 bit Editions Windows Server 2003 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions Microsoft Windows ME Microsoft Windows 2000
	BUS	PCI CC Range : Brainboxes range of PCI cards support 5V PCI slots and have been superceded by Brainboxes uPCI (universal Peripheral Com- ponent Interconnect) range. For every card in the CC range there is a matching card in the UC and PX range. If you still have a required for Brainboxes CC cards please get in touch.
Approvals	Industry Approvals	Microsoft Certified Gold Partner TAA
	Microsoft Approvals	
General	PCB Layers	4
	Power Consumption	300mA @ 5V, 500mA @ 12V
	Weight	0.094 kgKg
	Size	awaiting mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCI DUAL LPT Printer Port & RS232
		1 port RS232 on fly lead
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
	Made In	Manufactured in the UK by Brainboxes Winner 2005 European
Cher Ryannogres Ranges: PCT Expres	ss Bluetooth Serial Adapter Eth	Electronics Industry Awards "Manufacturer of the Year" ernet to Serial Adapter a te d' Peserial Fard LExpressed Serial Adapter VSB to Seria