



# ISA

## 2 Port RS232

### Features

- 2 RS232 Serial Ports
- COM1 - COM8
- Interrupts 2-7,10-12, 14-15
- 16 Byte FIFO on each port
- Utility disk with Sample programs, Test and Terminal software with source code
- Optional LPT1-3,interrupts 5 or 7, with full bi-directional capability, needs optional LPT adaptor cable
- Drivers for all popular operating systems

### Specifications

- Ports: 2 x RS232
- UART: 16550
- Baud rates: Up to 115,200
- Data Bits: 5,6,7 or 8
- Stop Bits: 1 or 2
- Parity: Odd, even, none, mark or space
- Power: 300mA @ 5V.  
50mA @ ±12V
- Weight: 0.12kg
- Size: 10.7 x 12.5cm

### Applications

- Modem Connectivity
- Remote Access Servers
- Instrument Control
- UPS Control
- Banking & Financial Sector

### Optional LPT Printer Port

The printer port can be set to bi-directional mode, for scanners, file transfers etc.  
The ports can be configured in DOS as LPT 1 to LPT 3.  
In Windows the ports can be configured to any logical port number using the Ports applet in the Control Panel.

### Description



This half size card provides 2 industry standard 9 pin RS232 serial COM ports. Each serial port may be jumper configured as COM1 - COM8 with interrupt line jumpers set to IRQ 2-7, 10-12, 14-15.  
An LPT port is available using the optional adaptor cable. CC-021 with one 9 pin and one 25 pin Male D connector is also available.

### Software

Serial Solutions Device Driver CD contains software for Windows Millennium, Windows 98, Windows 95, Windows NT4, Windows 3.x, DOS and OS/2.

Informative manuals and sample programs are supplied with full source code on CD!

For details of RS232, RS422 or RS485 Standards see:  
[www.brainboxes.com/standards](http://www.brainboxes.com/standards)



### ORDER

Description	Code
ISA 2PORT RS232	CC-523
ISA 2PORT RS232 (1x9, 1x25pin)	CC-021
LPT ADAPTOR CABLE	CC-032