



Features

- 2 RS232 Serial Ports
- Opticalisolation: 1500V DC 1000V AC
- COM1 - COM8
- Interrupts 2-7,10-12, 14-15
- 16 Byte fifo on each port
- Utility disk with Sample programs, Test and Terminal software with source code.
- LPT1-3, interrupts 5 or 7, need optional LPT adaptor cable.

Specifications

- Ports: 1x9pinRS232
1x25pin RS232
- Opto isolation: $\pm 1500V$
DC/1000V AC
- UART: 16550
- Baud rates: Up to 115,200
- Data Bits: 5,6,7 or 8
- Stop Bits: 1 or 2
- Parity: Odd, even, none, mark or space
- Power: 300mA @ 5V
50mA@ $\pm 12V$
- Weight: 0.12kg
- Size: 10.7 x 12.5cm

Optional LPT Printer Port

The printer port can be set to bi-directional mode, for scanners, file transfers etc.

The ports can be configured in DOS as LPT 1 to LPT 3. In Windows the ports can be configured to any logical port number using the Ports applet in the Control Panel.

ISA

2 Port Opto RS232

Description



This half size card provides 2 industry standard RS232 serial COM ports using one 9 pin and one 25 pin Male 'D' connector, both ports are optically isolated to 1500 Volts DC/1000 Volts AC. Each serial port may be jumper configured as COM1 - COM8 with interrupt line jumpers set to IRQ 2-7, 10-12, 14-15.

Software

Serial Solutions Device Driver CD contains software for Windows 98, Windows 95, Windows Millennium, Windows NT4, Windows 3.x, DOS and OS/2. Informative manuals and sample programs are supplied with full source code on CD!

For details of RS232, RS422 or RS485 Standard see: www.brainboxes.com/standards



ORDER

Description
ISA 2PORT OPTO RS232 (9 + 25pin)
LPT ADAPTOR CABLE

Code
CC-049
CC-032