



Features

- 8 RS232 Serial Ports
- COM1-COM4 plus many more
- Interrupts 2-7, 10-12 & 15
- Shared interrupt register allows all ports to share 1 interrupt thus conserving precious PC resources
- 16 Byte fifo on each port
- Sample Programs, Test & Terminal software - all with source code
- Fully moulded cable with Standard 9 or 25 way male 'D' connectors
- Drivers for all popular operating systems
- Guaranteed 100% compatible with the Digiboard PC/8

Specifications

- Ports: 8 x RS232
- UART: 16550
- Baud rates: Up to 115,200
- Data Bits: 5, 6, 7 or 8
- Stop bits: 1 or 2.
- Parity: Odd, even, none, mark, or space
- Power: 525mA @ 5V
130mA @ ±12V
- Weight: 0.30kg
- Size: 10x34cm

Information

SCO XENIX and UNIX are directly compatible with the AT Lynx card. Two cards per system allow up to 16 terminals to be supported. The shared interrupt mechanism guarantees the highest possible data transfer rates.

ISA

8 Port RS232

Description



This half size card provides 8 industry standard RS232 serial COM ports in a single ISA slot. A fully moulded "Octopus" cable terminated in either 9 or 25 pin male 'D' plugs ensures neat & easy connections.

Software

Serial Solutions Device Driver CD contains software for Windows Millennium, Windows 98, Windows 95, Windows NT4, Windows 3.x, DOS and OS/2.

Informative manuals and sample programs are supplied with full source code on CD!

For details of RS232, RS422 or RS485 Standards see: www.brainboxes.com/standards



ORDER

Description	Code
ISA 8PORT RS232 (8 x 9pin)	CC-098
ISA 8PORT RS232 (8 x 25pin)	CC-335