



### Features

- Three RS232 Serial ports
- COM1 - COM8
- Interrupts 2-7, 10-12 & 14 -15
- 16 Byte fifo on each port
- Utility disk with sample programs, test and terminal software with source code
- Drivers for all popular operating systems

### Specifications

- Ports: 3 x RS232
- UART: 16550
- Baud rates: Up to 115,200
- Data Bits: 5,6,7 or 8
- Stop Bits: 1 or 2
- Parity: Odd, even, none, mark or space
- Power: 300mA @ 5V  
50mA @ ±12V
- Weight: 0.12kg
- Size: 10.7 x 12.5cm

### Applications

- Modem Connectivity
- Remote Access Servers
- Instrument Control
- UPS Control
- Laplink docking port
- Banking & Financial Sector

### The 16550 UART

16550 UARTs provide a 16 byte input and 16 byte output FIFO hardware buffer for each serial port allowing high data rates without data loss or overrun errors in today's multi-tasking operating systems.

# ISA

## 3 Port RS232

### Description



The half size card provides three independent RS232 serial ports, using the standard ISA 9 pin Male D connectors. The three serial ports may be separately jumper configured as COM1 - COM8 with interrupt line jumpers set to IRQ 2-7, 10-12, 14-15. The card includes full 16 bit address decode for Windows 95 & 98.

### Software

Serial Solutions Device Driver CD contains software for Windows Millennium, Windows 98, Windows 95, Windows NT4, Windows 3.x, DOS and OS/2. Informative manuals and sample programs are supplied with full source code on CD!



### ORDER

Description  
ISA 3 PORT RS232

Code  
CC-118