



### Features

- 2 RS232 Serial Ports
- COM1 - COM8
- Interrupts 2-7,10-12, 14-15
- Line Drivers - 1 Mbit
- 64 byte fifo on each port

### Specifications

- Ports: 2 x RS232
- Baud rates: Up to 921,600
- Data Bits: 5, 6, 7 or 8
- Stop bits: 1 or 2
- Parity: o,e,n,m or s
- Power: 425mA @ 5V
- Weight: 0.12kg
- Size: 13cm x 8.5cm

### Applications

- RAS Server
- UPS Control
- Instrument Control
- Point of Sale High speed
- ISDN modems

# ISA

## 2 Port Velocity RS232

### Description



This is simply the highest performance 100% PC UART compatible RS232 card available today! The half size card provides two independent RS232 ports.

The UART clock can be set through software to provide maximum baud rates of either 921,600 baud, 460,800 baud, 230,400 baud, or 115,200 baud (standard PC).

### Software

Serial Solutions Device Driver CD contains software for Windows Millennium, Windows 98, Windows 95, Windows NT4, Windows 3.x, DOS and OS/2.

Informative manuals and sample programs are supplied with full source code on CD!



### ORDER

Description  
ISA 2PORT VELOCITY RS232

Code  
CC-124