












RoHS Compliant

CC-257

PCI DUAL RS232 TWIN 9 CONNECTORS

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 2 port RS232
- PCI 2.3
- 16 Byte Tx and 16 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options

PCI DUAL RS232 TWIN 9 CONNECTORS

Description

This half size card provides 2 industry standard 9 pin RS232 serial COM ports in a single PCI slot. By adding the optional LPT adapter cable, a parallel printer port becomes available. As PCI is fully Plug & Play compatible the operating system or Bios automatically configures card ensuring conflict free installation. Serial Solutions Device Driver CD contains software for Windows 7, Server 2008, Vista, Server 2003, XP, 2000, Millennium, 98, 95, NT4, Windows 3.x, DOS and OS/2. Informative manuals and sample programs are supplied with full source code on CD!

Brainboxes range of PCI cards support 5V PCI slots and have been superceded by Brainboxes uPCI (universal Peripheral Component Interconnect) range. For every card in the CC range there is a matching card in

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.











ORDER

Description

Code CC-257

PCI DUAL RS232 TWIN 9 CONNECTORS

PCI DUAL RS232 TWIN 9 CONNECTORS

CC-257Full Specification

Pin 2 RXD Pin 3 TXD Pin 4 DTR Pin 5 FIF Pin 5 GND Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI Pin 5 Pin 9 RI Pin 5 Pin 9 Pin 1 Pin 5 Pin 9 Pin 1 Pin 5 Pin 9 Pin 1 Pin 5 Pin 6 Pin 9 Pin 6 Pin 9 Pin 6 Pin 9 Pin 9 Pin 9 Pin 6 Pin 9 Pi	onnector FO size perating Distance able	2 x RS232 Connector DB9 9 Pin Male 16 RX FIFO + 16 TX FIFO EIA - RS232 Standard No Cable; Integrated Connector
Pin 2 RXD Pin 3 TXD Pin 4 DTR Pin 5 GND Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI Pin 6 Pin 9 Pin 9 Part Da Part	FO size perating Distance able	16 RX FIFO + 16 TX FIFO EIA - RS232 Standard
Pin 3 TXD Pin 4 DTR Pin 5 GND Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI Port Settings Bat 115,200 Pare Pare Pare Pare Pare Pare Pare Pare	perating Distance	EIA - RS232 Standard
Pin 5 GND Pin 6 DSR Pin 7 RIS Pin 8 CTS Pin 9 RI Port Settings 115,200 Par	ble	
Pin 8 CTS Pin 9 RI Port Settings Bat 115,200 Par		No Cable; Integrated Connector
115,200 Da	ud Rate	
> > > Par		115,200
	ata Bits	5,6,7 or 8
	rity	Odd, Even, None, Mark or Space
baud	op Bits	1 or 2
Flo	ow Control	
Tx/	/Rx Modes	Point to Point
	5 Compatibility	Microsoft Windows 7 32 bit & 64 bit Editions Windows Server 2008 32 bit & 64 bit Editions Windows Vista 32 bit & 64 bit Editions Windows Server 2003 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions
PCI		Microsoft Windows ME Microsoft Windows 2000
BU	JS	PCI CC Range: Brainboxes range of PCI cards support 5V PCI slots and have been superceded by Brainboxes uPCI (universal Peripheral Component Interconnect) range. For every card in the CC range there is a matching card in the UC and PX range. If you still have a required for Brainboxes CC cards please get in touch.
Approvals Inc	dustry Approvals	Microsoft Certified Gold Partner TAA
Min	icrosoft Approvals	
General	CB Layers	4
Por	wer Consumption	190mA @ 5V, 12mA @ 12V
We	eight	0.08 kgKg
Siz	ze	awaiting mm
Box Content Page	ckaging	Installation CD including manual, Microsoft signed drivers & utilities
Cal	ırd	PCI DUAL RS232 TWIN 9 CONNECTORS
		No Cable; Integrated Connector
Product Support Wa	arranty	Lifetime (online registration required)
Su		Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Additional	EM option	Available for bulk buy OEM
Elektra O5		Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year" Petra Spial Adapter at PCMC A Special Far C L Express Serial Adapter of USB to Serial

+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com