












# RoHS Compliant

# CC-275/ CC-279

## PCI LYNX 8 PORT RS232 8X25 PIN

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



#### **Features**

- 8 port RS232
- PCI 2.3
- 16 Byte Tx and 16 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### **Options**

CC-275. PCI LYNX 8 PORT RS232 8X25 PIN

CC-279 PCI LYNX 8 PORT RS232

#### Description

This half size card provides 8 industry standard RS232 serial COM ports in a single PCI slot. A fully moulded "octopus" cable terminated in eight 25 pin male 'D' plugs ensures neat & easy connections. As PCI is fully Plug & Play compatible the operating system or Bios automatically configures the card ensuring conflict free installation. Serial Solutions Device Driver CD contains software for Windows 7, Server 2008, Vista, Server 2003, XP, 2000, Millennium, 98, 95, NT4, Windows 3.x, DOS and OS/2. Informative manuals and sample programs are supplied with full source code on CD!

Brainboxes range of PCI cards support 5V PCI slots and have been superceded by Brainboxes uPCI (universal Peripheral Component Intercon-

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.









ORDER

Description

Code CC-275 CC-279

PCI LYNX 8 PORT RS232 8X25 PIN PCI LYNX 8 PORT RS232 8X9 PIN

# PCI LYNX 8 PORT RS232 8X25 PIN

### CC-275/ CC-279Full Specification

CC-273/ CC-279Full Specific	Cation	
Port	Ports	8 x RS232
Pin 1   DCD   RS232 Pinout (9 Pin Male)	Connector	DB25 Connector 25 Pin Male (CC-275) Connector DB9 9 Pin Male (CC-279)
Pin 2         RXD         Pin 1         Pin 5           Pin 3         TXD	FIFO size	16 RX FIFO + 16 TX FIFO
Pin 4         DTR           Pin 5         GND           Pin 6         DSR	Operating Distance	EIA - RS232 Standard
Fin 7   RTS   Pin 8   CTS   Pin 9   RT	Cable	8 port cable (78 way D - 25 Pin) (CC-275) 8 port cable (78 way D - 8x9 Pin) (CC-279)
Port Settings	Baud Rate	115,200
115,200	Data Bits	5,6,7 or 8
<b>&gt;</b> >>>	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1 or 2
	Flow Control	
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Microsoft Windows 7 32 bit & 64 bit Editions Windows Server 2008 32 bit & 64 bit Editions
		Windows Vista 32 bit & 64 bit Editions
		Windows Server 2003 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions
PCI <sup>*</sup>		Microsoft Windows ME
1 01		Microsoft Windows 2000
	BUS	PCI CC Range: Brainboxes range of PCI cards support 5V PCI slots and have been superceded by Brainboxes uPCI (universal Peripheral Component Interconnect) range. For every card in the CC range there is a matching card in the UC and PX range. If you still have a required for Brainboxes CC cards please get in touch.
Approvals	Industry Approvals	Microsoft Certified Gold Partner TAA
	Microsoft Approvals	Windows XP 32 bit & 64 bit editions
General	PCB Layers	4
	Power Consumption	300mA @ 5V, 50mA @ 12V (CC-275) 5V PCI 8 Port RS232 DB9 (CC-279)
	Weight	awaiting (CC-275) 0.112 kg (CC-279)Kg
	Size	null mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCI LYNX 8 PORT RS232 8X25 PIN
		8 port cable (78 way D - 25 Pin) (CC-275) 8 port cable (78 way D - 8x9 Pin) (CC-279)
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Other Brainboxes Ranges: PCI Express	Bluetooth Serial Adapter   Ether	rnet to Serial Adapter   PCMCIA Serial Card   ExpressCard Serial Adapter   USB to Serial

+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com