












RoHS Compliant

CC-431

PCI 3 PORT RS232

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 3 port RS232
- PCI 2.3
- 16 Byte Tx and 16 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options

CC-431. PCI 3 PORT RS232

Description

This half size card provides 3 industry standard RS232 serial COM ports in a single PCI slot, using the standard 9 pin Male 'D' connectors. As PCI is fully Plug & Play compatible the operating system or Bios automatically configures the card ensuring conflict free installation. Serial Solutions Device Driver CD contains software for Windows 7, Server 2008, Vista, Server 2003, XP, 2000, Millennium, 98, 95, NT4, Windows 3.x, DOS and OS/2. Informative manuals and sample programs are supplied with full source code on CD!

Brainboxes range of PCI cards support 5V PCI slots and have been superceded by Brainboxes uPCI (universal Peripheral Component Interconnect) range. For every card in the CC range there is a matching card in

Software

Microsoft signed drivers (easy installation & robust operation) for:

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.









ORDER

Description

PCI 3 PORT RS232

Code CC-431

PCI 3 PORT RS232

CC-431Full Specification

Port	Ports	3 x RS232
Pin 1 DCD RS232 Pinout (9 Pin Male)	Connector	Connector DB9 9 Pin Male
Pin 2 RXD Pin 1 Pin 5 Pin 3 TXD	FIFO size	16 RX FIFO + 16 TX FIFO
Pin 4 DTR Pin 5 GND	Operating Distance	EIA - RS232 Standard
Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 6 Pin 9	Cable	No Cable; Integrated Connector
Pin 9 RI		
Port Settings	Baud Rate	115,200
115,200	Data Bits	5,6,7 or 8
> > > >	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1 or 2
	Flow Control	
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Microsoft Windows 7 32 bit & 64 bit Editions Windows Server 2008 32 bit & 64 bit Editions
		Windows Vista 32 bit & 64 bit Editions
		Windows Server 2003 32 bit & 64 bit Editions
		Windows XP 32 bit & 64 bit Editions
PCI		Microsoft Windows ME Microsoft Windows 2000
	BUS	PCI CC Range : Brainboxes range of PCI cards support 5V PCI slots and
		have been superceded by Brainboxes uPCI (universal Peripheral Com-
		ponent Interconnect) range. For every card in the CC range there is a
		matching card in the UC and PX range. If you still have a required for Brainboxes CC cards please get in touch.
Approvals	Industry Approvals	Microsoft Certified Gold Partner TAA
Approvais	Microsoft Approvals	
	Wheresore Approvais	
General	PCB Layers	4
	Power Consumption	300mA @ 5V, 50mA @ 12V
	Weight	0.095 kgKg
	Size	awaiting mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCI 3 PORT RS232
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
SETTING SETTING	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
	ess -Bluetooth Serial Adapter Eth	ernet to Serial Adapter a technology awards invandracturer of the Year ernet to Serial Adapter a technology awards invandracturer of the Year ernet to Serial Adapter a technology awards invandracturer of the Year
+44(0) 151 220 2500 sales@brainboxes.com www.brainboxes.com		
1 1(0) 10 1 220 2000 Odioo@bidiliboxco.com		