







PM-120/PM-154

PCMCIA 1xRS422/485 1MBaud "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 1 port RS422/485
- PCMCIA socket size
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



PM-120: PCMCIA 1xRS422/485 1MBaud

PM-154 PCMCIA 1xRS422/485 RUGGED 1MBaud



Description

PC Card providing one RS422/485 serial port. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your laptop. The detachable cable allow the PC card to stay in the laptop without risk of damage during transit. Drivers for Windows 32 bit and 64 bit Operating Systems including Windows 95/98/2000, XP, Server 2003, Vista, Server 2008 and Windows 7.

Being mobile no longer limits your options. Standard and ruggedised card options to suit your needs.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support! Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows XP 32 bit 64 bit editions
- Windows 2000



As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.





ORDER	
Description	
PCMCIA 1xRS422/485 1MBaud	
PCMCIA 1xRS422/485 RUGGED 1MBaud	

Code	
PM-120	
PM-154	

+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com

PM-120/PM-154

PCMCIA 1xRS422/485 1MBaud

PM-120/PM-154: Full Specification

Port	Ports	1 x RS422/485
Pin 1 TXD- RS422/485 Pinout (9 Pin)	Connector	DB9 Connector - 9 Pin Male
Pin 2 TXD+ Pin 1 Pin 5 Pin 3 RTS-	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 4 RTS+ Pin 5 GND	Operating Distance	RS422/485 Standard 4000 ft : 1200 metres
Pin 6 RXD- Pin 7 RXD+ Pin 8 CTS Pin 6 Pin 9	Cable	Fully wired moulded cable
Pin 9 CTS+		
Port Settings	Baud Rate	921,600
921,600	Data Bits	5,6,7 or 8
\rightarrow \rightarrow \rightarrow \rightarrow	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	
	Tx/Rx Modes	Full Duplex, Half Duplex Autogating
Interface	OS Compatibility	Microsoft Windows 7 32 bit 64 bit Editions
PCMCIA		Windows Vista 32 bit 64 bit Editions Windows XP 32 bit 64 bit Editions
		Microsoft Windows 2000
	BUS	PCMCIA
Approvals	Other Approvals	AEO C-TPAT Microsoft Certified Gold Partner WEEE RoHS
	Microsoft Approvals	Microsoft Certified Gold Partner
		Windows 7 32 bit 64 bit Editions Windows Vista 32 bit 64 bit edi- tions
		Windows XP 32 bit 64 bit editions Windows 2000
General	PCB Layers	4
General	Power Consumption	100mA @ 5V
	Weight	0.026 kg
	Size	PCMCIA Type II: 85l x 54w x 5h mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
box content	Card	PCMCIA 1xRS422/485 1MBaud
		Fully wired moulded cable
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Verst Vinst		
Additional	OEM option	Available for bulk buy OEM
+ * +	Made In	Manufactured in the UK by Brainboxes Winner 2005 European
Elektra O5 European Electronics Industry Awards		Electronics Industry Awards "Manufacturer of the Year"
WINNER * * Manufacturer of the Year * *	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume
Made in the UK		users. More Info: sales@brainboxes.com